



Condor/Cobra Series

The Phoenix Condor 20 and Cobra 35 are all designed to provide extreme security protection for both domestic and business use.

- **Security Protection** - Tested to the prestigious European EN1143-1 Security Standard.
 - Condor 20** - Grade II has a recommended Insurance rating of £17,500 cash or £175,000 valuables*
 - Cobra 35** - Grade III has a recommended Insurance rating of £35,000 cash or £350,000 valuables*
- **Key Locking** - Condor fitted with high security double bitted VDS Class I keylock and Cobra fitted with VDS Class II keylock.
- **Electronic Lock** - Fitted with high security VDS class I (SECU SELO-A) electronic lock with time delay function, Euro Grade II. Euro Grade III safes fitted with VDS class II (SECU SELO-B) electronic lock with Time delay, multi user, dual control and audit trail.
- **Fixing** - Ready prepared for floor fixing, with fixing bolts for concrete supplied.
- **Construction** - Double wall construction with profiled infill, anti drill plates and re-locker protection for the door provide a safe of great strength.
- **Colour** - Finished in a high quality scratch resistant paint Ral9003.

OPTIONAL EXTRAS AVAILABLE
 Height adjustable shelves
 Secu Changeable Key Lock
 Secu Electronic Lock and Key Lock
 Cut key only available at time of order unless Secu changeable key lock option is specified
 Electronic Time Delay Combination Lock
 Electronic Time Delay and Key Lock
 Key Rack Set - 80 keys (HS2021)
 Key Rack Set - 200 keys (HS2022)
 Key Rack Set - 280 keys (HS2023)

Shown with optional key rack



Shown with electronic lock



	HS2020E HS3530E 				
	£17,500 €26,000	£35,000 €52,500	FITTED WITH KEYLOCK	FITTED WITH ELECTRONIC LOCK	OPTIONAL CHANGEABLE KEYLOCK
	Condor 20	Cobra 35			

*Ratings are approximate only and may vary due to area conditions and location. Please check with your underwriter.

Body

The inner and outer bodies are constructed from high grade steel electrically welded together to form one solid unit with minimum thickness of 60mm. The space between the inner and outer body contains advanced anti-penetration materials.

Door

The door is constructed with double steel walls containing a unique Anti Penetration material in total, forming a minimum of 100mm barrier of defensive strength.

Boltwork

All sizes have 3 way moving espagnolette boltwork with 30mm bolts securing into the top and bottom door frame. In addition the two hinge dog bolts at the rear give added strength and provide a clean cut, modern appearance disguising its strength.

Locking

The entire locking area is covered by hardened manganese steel anti drill plates and a "live" anti explosive relocking device, which is permanently on guard to protect against even the most determined attack.

Model	External Dimensions HxWxD	Internal Dimensions HxWxD	Door swing / door handle depth	Weight	Capacity	No. of shelves
HS2021K/HS2021E	440 x 440 x 460mm	320 x 320 x 295mm	370mm / 60mm	75 kgs	30 ltr	1
HS2022K/HS2022E	780 x 440 x 460mm	660 x 320 x 295mm	370mm / 60mm	117 kgs	62 ltr	2
HS2023K/HS2023E	780 x 600 x 460mm	660 x 480 x 295mm	530mm / 60mm	143 kgs	93 ltr	2
HS2024K/HS2024E	1200 x 600 x 510mm	1080 x 480 x 345mm	470mm / 60mm	209 kgs	179 ltr	2
HS2025K/HS2025E	1500 x 800 x 570mm	1380 x 680 x 400mm	670mm / 60mm	338 kgs	375 ltr	3
HS3531K/HS3531E	620 x 440 x 530mm	455 x 275 x 300mm	370mm / 60mm	160 kgs	38 ltr	1
HS3532K/HS3532E	850 x 600 x 530mm	685 x 435 x 300mm	530mm / 60mm	256 kgs	90 ltr	2
HS3533K/HS3533E	1200 x 600 x 530mm	1035 x 435 x 300mm	530mm / 60mm	312 kgs	135 ltr	2
HS3534K/HS3534E	1500 x 800 x 530mm	1335 x 635 x 300mm	670mm / 60mm	473 kgs	255 ltr	3

Door aperture is reduced by 20mm due to frame.

All weights and sizes are approximate.

All Phoenix Safes come with a full two year materials and labour warranty.

Phoenix policy is one of constant improvement. We therefore reserve the right to alter any part of the specification achieved in this publication without incurring any obligation.